










Grummets mit Fasereinlage

Neigungswinkel β	-	-	-	0°-45°	>45°-60°	0°-45°		>45°-60°	>45°-60°
Seil-Nenn- \emptyset mm									

Tragfähigkeit in kg

12	2100	1650	4200	2950	2100	2950	2350	2100	1650
15	3200	2500	6400	4500	3200	4500	3600	3200	2500
18	4650	3700	9300	6500	4650	6500	5200	4650	3700
21	6300	5000	12600	8800	6300	8800	7000	6300	5000
24	8300	6500	16600	11600	8300	11600	9300	8300	6600
27	10500	8500	21000	14700	10500	14700	11800	10500	8400
30	11500	9000	23000	16100	11500	16100	12900	11500	9200
33	14000	11000	28000	19600	14000	19600	15700	14000	11200
36	16500	13000	33000	23100	16500	23100	18500	16500	13200
39	19500	15500	39000	27300	19500	27300	21800	19500	15600
42	22500	18000	45000	31500	22500	31500	25200	22500	18000
48	29500	23500	59000	41300	29500	41300	33000	29500	23600
54	37500	30000	75000	52500	37500	52500	42000	37500	30000
60	46000	37000	92000	64400	46000	64400	51500	46000	36800