











Anschlagseile mit Stahleinlage

Neigungswinkel β	-		0°-45°		>45°-60°		0°-45°		->45°-60°		-	
												
Seil-Nenn-Ø mm												
Tragfähigkeit in kg												
8	750	600	1050	850	750	600	1550	1100	1500	1200		
10	1150	900	1600	1300	1150	900	2400	1700	2300	1850		
12	1700	1350	2300	1900	1700	1350	3550	2500	3400	2700		
14	2250	1800	3150	2500	2250	1800	4800	3400	4500	3700		
16	3000	2400	4200	3400	3000	2100	6300	4500	6000	4800		
18	3700	3000	5200	4200	3700	2500	7800	5650	7400	6000		
20	4600	3700	6500	5200	4600	3700	9800	6900	9200	7350		
22	5650	4500	7800	6300	5650	4500	11800	8400	11300	9000		
24	6700	5400	9400	7600	6700	5400	14000	10000	13400	10600		
26	7800	6200	11000	8700	7800	6200	16500	11500	15600	12500		
28	9000	7200	12500	10000	9000	7200	19000	13500	18000	14500		
32	11800	9500	16500	13300	11800	9500	25000	17700	23600	19000		
36	15000	12000	21000	16800	15000	12000	31500	22500	30000	23500		
40	18500	15000	26000	21000	18500	15000	39000	28000	37000	30000		
44	22500	18000	31500	25000	22500	18000	47000	33500	45000	36000		
48	26000	21000	37000	29000	26000	21000	55000	40000	52000	42000		