










Grummets mit Stahleinlage

Neigungs- winkel β	-	-	-	0°-45°	>45°-60°	0°-45°		>45°-60°	>45°-60°
									
Seil- Nenn-Ø mm									
Tragfähigkeit in kg									
12	2200	1750	4400	3000	2200	3000	2400	2200	1750
15	3400	2700	6800	4750	3400	4750	3800	3400	2700
18	4900	3900	9800	6850	4900	6850	5500	4900	3900
21	6700	5350	13400	9400	6700	9400	7500	6700	5350
24	9000	7200	18000	12600	9000	12600	10080	9000	7200
27	11500	9200	23000	16100	11500	16100	12900	11500	9200
30	14000	11200	28000	19600	14000	19600	15700	14000	11200
33	17000	13600	34000	23800	17000	23800	19000	17000	13600
36	20000	16000	40000	28000	20000	28000	22400	20000	16000
39	23500	18800	47000	32900	23500	32900	26300	23500	18800
42	27000	21600	54000	37800	27000	37800	30200	27000	21600
48	35500	28400	71000	49700	35500	49700	39800	35500	28400
54	45000	36000	90000	63000	45000	63000	50400	45000	36000
60	55500	44400	111000	77700	55500	77700	62200	55500	44400